

PE PROTECTION TAPE

PROPERTIES

Black 115 micron PE protection tape coated with a scuff resistant rubber based adhesive.

The product adheres well to various substrates including glass and aluminium and removes cleanly with no adhesive residue. Good conformability when adhering to complex shapes.

The tape is suited for protecting anodised or powder coated aluminium window frames during storage, transport and installation.

UV Resistant for up to 6 months.



FEATURES

- Medium tack adhesive
- Provides excellent temporary surface protection
- Easy unwind in narrow and wide width rolls
- Available in a variety of widths

| PROPERTIES | UNIT | SPECIFICATION | TEST METHOD |
|-------------------|---------|---------------|-------------|
| Total Thickness | mm | 0.115 | ASTM-100 |
| Tensile Strength | KG/25mm | 1.20 | ASTM-100 |
| Elongation | % | 150+ | ASTM-100 |
| Adhesion to Steel | GF/25mm | 250+ | ASTM-100 |

Terms & Conditions

This product should be applied to a clean and dry surface. The adhesive of the product must not be exposed direct to the sunlight when applied. The above figures represent average values. The selection of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our product and specifications.