



Diamond Guard 714 Black is an excellent PVC aluminium protection tape. 714 Black is UV and moisture resistant, it is designed to remove cleanly without leaving residue

## Benefits

- Easily applied by hand - no specialist equipment required.
- Self adhesive, does not require additional fixing.
- Stays in place - once smoothed into position Diamond Guard 714 Black will not fall away.
- Forms an effective barrier against splashes and prevents scratching.
- Removes cleanly - the specially formulated adhesive will not leave residue.
- UV protected - can be left for up to 3 months.
- Versatile - can be used on various smooth and textured surfaces.



## Application Instructions

- Obviously, adhesion will be reduced on dusty surfaces. Cleaning prior to use is recommended.
- Avoid stretching tape during application.
- Diamond Guard 714 Black must be removed after a maximum of 12 weeks.
- Always check that Diamond Guard 714 Black is stuck firmly to substrate before commencing work.
- A test area is always recommended prior to full application.
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.

## Uses

- Protecting aluminium extrusion
- Protecting stainless steel



SPECIFICATIONS	Diamond Guard 714 Black	
Colour	Black	
Film Thickness	0.12mm	
Sizes	96 x 66mm, 48 x 66mm, 24 x 66mm, 18 x 66mm, Custom widths (max 1220mm) x 66mm	
Carton Quantity	96mm roll = 18 rolls per carton 24mm roll = 72 rolls per carton	48mm roll = 36 rolls per carton 18mm roll = 96 rolls per carton
Application Conditions	The surface must be free from oil, dust, solvents and separating agents	
Resistance	Against moisture: Good. Against oil: Moderate. Against solvent: Good. Against UV: Good	
Storage Conditions	Room temp. Max 12 months from date of manufacture	

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technical changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Any warranty applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.